

**TECTORIUS® TEC-EIZE™**

Thread Lubricant and Anti-Seize Compound

**DESCRIPTION:**

Tec-Eize thread lubricants and anti-seize compounds are a group of materials specially designed for fasteners and components to reduce friction, increase job efficiency, and facilitate installation and removal processes over extended periods.

This product family is intended for mass pre-application onto fasteners, fittings and components—in situations where automated installation will occur later, and on-site use of materials is not possible or ideal.

**APPLICATIONS:**

- » Tri-lobular thread forming bolts
- » Thread cutting fasteners of all types
- » Springs and spring clips
- » Gall susceptible substrates (i.e. aluminum and stainless steel)
- » Seat and window guides
- » Many more

**PRODUCT FEATURES:**

- » Reduces effort required for installation of fasteners and additional components by as much as 75%.
- » Reduces surface wear.
- » Squeak and rattle reduction.
- » Eliminates galling and installation torque 'chatter'.
- » Available in several grades with varying degrees of lubrication, color, and application methods.
- » Available in solvent based liquid or semi-solid.
- » Adjustable viscosity for widely varying part sizes and applications.
- » Application as a solvent based liquid for most common machinery, or in a molten state for optimum application speed.
- » Extended, indefinite shelf life.

Specific formulations of Tec-Eize™ meet or exceed the performance requirements of the following standards:

**AUTOMOTIVE:**

- Ford Motor Company WSA-M9G20B
- Chrysler– WS 4592
- GM– 9986167

\*The information provided is based on technical data that Tectorius believes to be reliable. Since we cannot anticipate or control the various conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. Therefore, the product is sold without warranty expressed or implied.

Tectorius® · 56732 Mound Rd. · Shelby Twp., MI 48316 · Phone: 586-232-3999 · Fax: 586-232-3991  
Visit our website at [www.tectorius.com](http://www.tectorius.com) · email: [info@tectorius.com](mailto:info@tectorius.com)

Tectorius® and all Tectorius products denoted with ® or ™ are trademarks or registered trademarks of Maelstrom Chemical Technologies, LLC or its affiliates. All rights reserved.



# TECTORIUS® TEC-EIZE™

Thread Lubricant and Anti-Seize Compound

## SPECIFICATIONS:

Grade:	630	631	632	633
<b>Color</b>	Black	Bronze	Black	White
<b>Primary Usage</b>	Anti-Seize/ High Temp.	Anti-Seize/ High Temp.	Anti-Seize/ Specialty	Lubrication/Anti-Seize
<b>Typical Use</b>	Serviceable Parts	Serviceable/ High Wear Parts	Serviceable/ Specialty	Thread Forming, Gall Prevention, Lubrication
<b>Temperature Range</b>	Up to 1200° F	Up to 1200° F	>1500° F	Up to 600° F
<b>Lubricity</b>	Medium	Medium	Medium	Very High
<b>Special Features</b>	General Purpose	High Pressure	High Temperature	Non Metallic, Non Conductive

Note: If you don't see the product you are looking for, ask us about our **Tec-Slip™ dry film lubricant** coatings for other pre-applied lubrication options. These may also be effective for your specific application.

\*The information provided is based on technical data that Tectorius believes to be reliable. Since we cannot anticipate or control the various conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. Therefore, the product is sold without warranty expressed or implied.