



TECTORIUS® TEC-SOLV™ 1050

Surface Prep/Adhesion Primer

DESCRIPTION:

Tec-Solv™ is a surface preparation and adhesion primer that increases the bonding ability of challenging substrates such as glass, plastics, metal silicone rubber and polytetrafluoroethylene, a Teflon® type material. Tec-Solv can be applied by brushing, spraying or wiping the surface. It contains no chlorinated or fluorinated solvents.

PRODUCT FEATURES:

- » Contains no chlorinated or fluorinated solvents.
- » Brush on, wipe or spray.
- » Increases bonding abilities.

SPECIFICATIONS:

Base Compound	Organic Solvent Blend
Appearance	Colorless liquid
Viscosity	1 cps
Specific Gravity	0.7
Flash Point	25°F
Shelf Life	12 months unopened
Boiling Point	210°F
Odor	Pungent
Vapor Density	Not available
Percentage Volatiles (by weight)	>99% @ 70°F
RoHS Compliant	Yes
Competing Products	Dow Betaclean 3350** Cyberbond Boost 6070

Storage

Tec-Solv is **highly flammable** and should be stored away from heat, open flame, or ignition sources. Products should be stored unopened, in a cool, dry place out of direct sunlight.

Health Precautions

Skin contact: Wash exposed areas with large amounts of soap and water for 15-20 minutes.

*The information provided is based on technical data that Tectorius believes to be reliable. Since we cannot anticipate or control the various conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. Therefore, the product is sold without warranty expressed or implied.

**Dow and Betaclean are registered trademarks of the Dow Chemical Company

Tectorius® · 56732 Mound Rd. · Shelby Twp., MI 48316 · Phone: 586-232-3999 · Fax: 586-232-3991
Visit our website at www.tectorius.com · email: info@tectorius.com

Tectorius® and all Tectorius products denoted with ® or ™ are trademarks or registered trademarks of Maelstrom Chemical Technologies, LLC or its affiliates. All rights reserved.